

Solvoya® D5970-X

Edition 04-2020

Solvoya® D5970-X is a short oil Non-dry alkyd resin based on a mix of Castor oil & Linoleic rich fatty acid - available in solids from 60% to 70% ± 1% in Xylene

Mode of application: Bake, NC and/or catalyzed dry.

PERFORMANCE & APPLICATIONS

- Excellent adhesion and scratch resistance
- Excellent mechanical performance
- Good sanding and filling properties .
- Used for NC polishing lacquers for furniture
- Recommended for clear, pigmented PU-finishes
- Recommended for sealers for metal and wood
- Suitable for acid curing finishes

SUPPLY SPECIFICATIONS

• Delivery form	70.0 ± 1%
• Dilution form	60.0 ± 1%
• Acid value mg KOH/gm solid	15.0 max.
• Gardner viscosity at 25°C	Approx. Z2-Z4 at 60%
• Brookfield approx. viscosity at 25°C	Approx. 4,600 CP at 60%
• OH-Content (Per solids)	4.00%
• Gardner Color Scale DIN EN ISO 6271-1	6.0 max.

TYPICAL COMPOSITION

• Phthalic anhydride content	38%
• Type of oil	Castor oil & Linoleic rich fatty acid
• Oil Content	41%
• Type of Polyol	Penta
• Type of Solvent(s)	Xylene

SPECIFIC PROPERTIES

• Aliphatic hydrocarbon	Insoluble	• Zinc white	Incompatible
• Aromatic hydrocarbon	Soluble	• Red Lead	Incompatible
• Chlorinated hydrocarbon	Soluble	• Nitrocellulose	Compatible
• Alcohols	Limited solubility	• Chlorinated rubber	Incompatible
• Esters	Soluble	• Stand oil	Limited compatibility
• Ketones	Soluble	• Isocyanate	Compatible
• Glycol-ethers & esters	Soluble	• Urea/melamine resins	Compatible

STORAGE

Solvoya® D5970-X is stable at temperatures up to 30 °C when packed in original containers, Exposure to sun shine should be avoided.

STABILITY

Solvoya® D5970-X is stable for more than 24 months from the date of production mentioned on the pack of each patch, with reference to the above mentioned storage conditions.

REMARKS

- For Ideal Drying time test results, EBCA recommends testing after 48 hours from adding the driers to the paint (min. 24 hours).
- The combinations must be tested for their compatibility

Egyptian British Company maintains Material Safety Data sheets (MSDS) on all of its products. These contain important information that you may need to protect your employees and customers against any known health and safety hazards associated with our products. We recommend you obtain copies of MSDS for our products, from our technical representative, and obtain copies of MSDS from your suppliers of other raw materials used with our products.